

## RUEDAS Y NEUMÁTICOS PARA REMOLQUES DE COCHES Y OTROS VEHÍCULOS ARRASTRADOS



Código	Neumático	Rueda	Desplaz.	Ataque	Medidas en mm.		Carga/Velocidad*	Presión (bars)	Peso (kgs.)
					ancho	diámetro			
CJT08"005	3.50-8" 4PRC TL	2,50-8"	0	4/ 58,5-98	89	384	6N	2,5	3,5
CJT08"001	4.00-8" 4PR TL	5.50-8"	0	4/ 58,5-98	110	425	62N	4	3,7
CJT08"003	16.5X6,5-8" 4PR TL				165	415	64M	3,1	5,8
CJT10"004	4.50-10" 4PR TL				130	490	69M	7	
CJT10"003	5.00-10" 4PR TL	3.50-10"	0	4/ 58,5-98	145	515	72N	3,5	7,5
CJT10"006	5.00-10" 8PR TL	145	515				84M	4	8
CJT10"002	145-10" 4PR TL	3.50-10"	0	145	485	68M	2,5	7	
CJT10"007	20.5X8.0-10" 10PR TL	6.00-10"	0	200	515	96M	6	15	
CJT13"002	135/80R - 13" TL	4J-13"	30	4/ 58,5-98	135	546	69N	2,5	10,5
CJT13"003	145/80R - 13" TL	4J-13"			145	562	78N		11
CJT13"004	155/80R - 13" TL	4J-13"			155	578	79N		12
CJT13"005	165/80R - 13" TL	4J-13"			165	594	83T		12,5
CJT13"006	175/70R - 13" TL	4J-13"			175	576	82T		13
CJT13"007	195/50R - 13" TL	61/2J-13"	5/66.6-112	195	526	104/102N	6,75	-	
CJT13"008	195/50R - 13" TL	61/2J-13"				5/94x140	195	526	104/102N
CJT14"003	185/70R - 14" TL	51/2J-14"	30	4/ 58,5-98	185	616	88H	2,5	18
CJT14"005	185R - 14" 8 PR CAR.	5J-14"	0	5/94x140	185	655	102/100Q	4,5	20
CJT14"006	205R - 14" 8 PR CAR	5J-14"	0	5/94x140	205	686	109/107R		21
CJT15"006	235/75R - 15" TL	6J-15"	30	6/110x139.7NS	235	733	105S		22
CJT16"008	215/80R - 16" TL	5.50F-16"	46	5/115.2x165.1LR	215	750	115/112R	27	
CJT16"009	215/80R - 16" TL	6J-16"	30	6/110x139.7NS	215	750	115/112R	29	

\*Ver tabla Índices de carga y velocidad